



xS-710

Semi-Rugged Tablet



Operating System

Windows® 8.1 PRO / Windows® 10 IoT Enterprise

CPU

Intel® Braswell Refresh N3010 TDP:4W

Display

10" 800 x 1280 - 16:10 350nits (typical)

Screen

10 points multi-touch Projected Capacitive touch screen
3 physical buttons (power, Windows hotkey, screen rotate)

RAM

2GB DDR3L on board, MAX support 8GB

ROM

32GB / 128GB

Camera

2MP Front camera
5MP Rear camera + auto focus (optional)

Network

3G / 4G (optional)
Wi-Fi 802.11 a/b/g/n/AC
Bluetooth® combo with WLAN (support BT 4.1 / 4.2, BT SIG)

I/O Interface

USB 3.0 x2
headphone out x1
Ø3.5 headphone/microphone combo jack, iPhone type
power jack 19V x1
micro SD slot x1, SDXC type, (SD 4.0)
pogo pin x1, female, U2, for docking
pogo pin x1, female, U2, for extra device
stereo type 1W x2

Applications

Barcode Scanner software decoding
NFC/RFID (ISO/IEC 14443 A/B, 15693/18092)
light sensor, E-compass sensor, G-sensor, Gyro sensor

Adapter

adapter 40W - 19V

Battery

battery 1 Li-Polymer 38Wh, pack swappable
battery operation: up to 8.7 hours (follow JEITA v2.0)
RTC battery: 1 yrs (rechargeable)

Dimension

274 x 186.5 x 13.5 mm

Weight

0.760 Kg

Rugged Feature

IP54
MIL-STD-810G (1.2m drops)

Operating Temperature

0°C ~ 40°C

Storage Temperature

-20°C ~ 60°C

Inbox Accesories

hand strap (optional)
shoulder strap (optional)
VESA mount (optional)
RJ45 (optional)
smart card reader (optional)
office dock (optional)